

# PRODUCT DATA SHEET P7R Core (C32)









# P7R Core

### PRODUCT DESCRIPTION

The versatile P7R Core flashlight offers exceptional power and forward-thinking technologies like the Smart Light Technology for custom light functions. Thanks to our Flex Sealing Technology, the P7R Core is protected against dust and water, and can even handle permanent submersion. Our patented Advanced Focus System works with up to one meter of water depth. This makes the P7R Core the ideal flashlight for every occasion.

- Advanced Focus System for efficient, precise flood and spot lighting
- Smart Light Technology for custom light functions
- High protection against dust and water (IP68) through Flex Sealing Technology
- Constant Light for constant luminous flux over a long period of time
- Convenient charging of the battery with Magnetic Charge System

| TECHNICAL DATA               |                      |
|------------------------------|----------------------|
| Length defocused [mm]        | 158                  |
| Length focused [mm]          | 165                  |
| Head diameter [mm]           | 35                   |
| Tube diameter [mm]           | 27                   |
| Weight incl. batteries [g]   | 202                  |
| Weight without batteries [g] | 131                  |
| Focus function               | Yes                  |
| Head material                | Aluminum alloy       |
| Tube material                | Aluminum alloy       |
| Optic                        | Plastic lense (PMMA) |
| Cartridge                    | No                   |
|                              |                      |

| POWER SUPPLY                 |                      |
|------------------------------|----------------------|
| Power source type            | Rechargeable battery |
| Battery quantity             | 1                    |
| Battery type                 | Li-ion               |
| Battery replaceable          | Yes                  |
| Total battery voltage [V]    | 3.7                  |
| Total battery capacity [mAh] | 4800                 |
| Total battery energy [Wh]    | 17.76                |
| Rechargeable                 | Yes                  |
| Charging time [min]          | 270                  |
| Energy modes                 | Constant Light       |
| Energy status indicator      | Battery Indicator,   |
|                              | Charge Indicator,    |
|                              | Low Battery Warning  |

### FURTHER SPECIFICATIONS

| IP class                       | IP68       |
|--------------------------------|------------|
| Drop test (drop height) [m]    | 2          |
| Maximum operating depth [m]    | 1.5        |
| Working temperature range [°C] | -20 to +40 |

#### LIGHT FUNCTIONS

Blink, Boost, Low Power, Mid Power, Power, Position, S.O.S., Strobe

| LIGHT SOURCE                |              |
|-----------------------------|--------------|
| Amount LEDs                 | 1            |
| LED type                    | Xtreme LED   |
| Color                       | White        |
| Color temperature [K]       | 6000 to 7500 |
| Color rendering index (CRI) | 70           |

| LIGHT VALUES          | 5     |       |           |           |
|-----------------------|-------|-------|-----------|-----------|
| ANSI – Constant Light | Boost | Power | Mid Power | Low Power |
| Light output [lm]     | 1400  | 1000  | 440       | 15        |
| Beam distance [m]     | 300   | 210   | 130       | 15        |
| Run time [h]          |       | 2     | 4         | 90        |

#### SWITCH

Front Switch

#### **FEATURES**

Dimmable , Transportation lock , Flicker Free, Memory Function, Back-Up Light

#### TECHNOLOGIES

Advanced Focus System, Sart Light Technology, Magnetic Charge System, Emergency Light, Temperature Control System, Flex Sealing Technology, Multi-Core Optics



# -P7R Core

## ACCESORIES

| PRODUCT CATEGORY           | ITEM NUMBER | PRODUCT NAME                              |
|----------------------------|-------------|---|
| Fastenings / Brackets      | 0362        | Universal Mounting System                 |
| Color filter / Signal caps | 502238      | Color Filter Set 35.1mm                   |
| Color filter / Signal caps | 502237      | Signal Cone 35.1mm                        |
| Color filter / Signal caps | 502243      | Signal Cone W 35.1mm                      |
| Pouches / Holster          | 0342        | Pouch Type G                              |
| Fastenings / Brackets      | 502251      | Lamp Adapter Type D                       |
| Fastenings / Brackets      | 7799-PT     | Universal Mounting Bracket Type B         |
| Charger / Cable            | 502258      | Wall Mount Type B                         |
| Charger / Cable            | 502260      | Charging Station Type B                   |
| Battery                    | 502262      | 21700 Li-ion Rechargeable Battery 4800mAh |
|                            | 502127      | Powerbank Flex10                          |
| Charger / Cable            | 502265      | Magnetic Charging Cable Type A            |
| Charger / Cable            | 0380        | USB Car Charger                           |
| Charger / Cable            | 502271      | USB Adapter 2.4A                          |
| Pouches / Holster          | 502263      | Case Type A                               |
| Pouches / Holster          | 502264      | Case Type B                               |
| Pouches / Holster          | 502269      | Leather Pouch Type D                      |
| Fastenings / Brackets      | 501033      | Magnetic Mount                            |
| Pouches / Holster          | 0323        | Tactical Professional Holster Type B      |
|                            | 502511      | Powerbank Flex5                           |

